



SPECIFICATIONS

Interior dimensions	L52.0 x W14.5 " x H6.0" L1321mm x W368mm x H152mm
Exterior dimensions	L55.1" x W17.3" x H6.6" L1399mm x W440mm x H168mm
Weight (empty)	21.6 lbs I 9.8 kg
Lid depth	1.6" I 41mm
Base depth	4.4" I 111mm
Max buoyancy	175 lbs I 79.4 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	No
Watertight	Yes
Warranty	Conditional lifetime guarantee

CERTIFICATIONS

- IPX7 INGRESS PROTECTION - WATERPROOF
- IP6X INGRESS PROTECTION - DUSTPROOF
- ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
- ASTM D-4169 DC-18 - DROP TEST (48cm(19") min.)
- ASTM D-4169 DC-18 - VIBRATION
- ASTM D-4169 DC-18 - RAINFALL
- MIL-STD-810F - IMMERSION (1 meter (3.28 ft))

MATERIALS

- **Case shell** – NK-7 high impact polypropylene
- **Latches** – Nylon 66
- **Handles** – NK-7 high impact polypropylene I TPE
- **Purge valve** – Nylon 66 I Gore® membrane I Silicone washers
- **Pins/hardware** – 304 stainless steel
- **Gasket** – EPDM
- **Wheels** – Polyurethane I Polycarbonate

Copyright © 2019 Plasticase inc. All rights reserved.

plasticase

NANUK™
PROFESSIONAL PROTECTIVE CASES

LONG SERIES 995

STANDARD FEATURES

1 - TSA Powerclaw latching system
2 - Waterproof IP67 rated
3 - Impact resistant NK-7 resin
4 - Reinforced metal padlock holes
5 - Tie down eyelets
6 - Stackable
7 - Polyurethane wheels
8 - Spring loaded top handle
9 - Soft grip handle stay
10 - Automatic pressure release valve
11 - Removable lid
12 - Lid Stopper 110˚
13 - 100% stainless steel hardware
14 - Conditional lifetime guarantee



AVAILABLE COLORS


Black 0001


Olive 0006


Graphite 0007


Tan 0000

AVAILABLE OPTIONS


Multilayer cubed foam


TSA approved padlock

CUSTOM OPTIONS


Custom printing



Custom label


Custom foam

Copyright © 2019 Plasticase inc. All rights reserved.

plasticase